Commercial &
Industrial Lighting

EXTERNAL
DIVER CANOPY

150W

EXTERNAL DRIVER PLATE CANOPY

KL-CP-150W-H3-M2-N-XX

DESCRIPTION:

Good fit for the gas station canopy and hotel portico for bright and secure and safe under canopy lighting. Effiecint and replaces existing 320w or 400w MH. The LED board is 23" squre cover most of the sizes of the exisitng big old box canopies and not requred to repaint. also light weight LED part is easy to mount and separate driver with conduit makes it so easy and clean look install for installer.use high quality mean well driver.

APPLICATIONS:

yard, dock, backyard, barns, farms, alleyways, roadway, parking lots, sidewalk, porch, building wall, etc.

SPECIFICATION FEATURES

LISTING:

ETL, DLC

WARRANTY:

5 Yrs Warranty

SUITABLE FOR WET LOCATIONS:

YES

ORDER INFORMATION

KL	CP	WATTAGE	H3	M2	N	CCT
KL	CP	150W	H3	M2	N	40K: 4000K 4K5: 4500K 50K: 5000K

DRIVER INFO

Type:	Constant Current
100-277Vac:	Yes
277-480Vav:	No
Input Watts:	150W
Distribution	120 degrees

PRODUCT FEATURES

- Description: 150W LED Canopy
- 15" Lens Cover, Offers Brighter Light Distribution
- Universal 100-277V
- Mercury Free: no UV
- Heavy-duty cast aluminum housing; rust and corrosion proof.
- Polyester powder coating
- Equivalent 400-600W HID/MH/HPS
- 5 Year Limited Warranty

Krut LED LLC - 111 Preamble Ct, Anderson, SC-29621 - Ph: 864-401-8156
Website: www.krutled.com - Email: sales@krutled.com

EXTERNAL DRIVER PLATE CANOPY

KL-CP-150W-H3-M2-N-XX

LIGHTING PARAMETERS

Product Code	KL150CPXX-SLIM
Wattage	150W
Color Temperature	4000K, 4500K, 5000K
Application	Outdoor
CRI	>70
THD	≤20%,
Material	Rohs compliant.
Input Voltage	100-277VAC 50/60Hz
Light Type	External Diver Canopy
Lumen	19000~20000
Lumen Efficancy	130~140 Lm/ W
Operating Humidity	20%-90% RH
Operating Temperature	-30°C To 50°C
Lifespan	50000 Hrs
Power Factor	≥0.9
Warranty	5 Years
Water Proof Rating	Suitable for Wet Location

PRODUCT FEATURES

- Slim Design H=0.59"
- Heavy-duty die cast aluminum housing; rust and corrosion proof;polyester powder coating
- Diffusor: High light transmittance & Polycarbonate with UV
- LEDs: Top grade LED, high-output,long-life;
- Heat Sink:Aluminium sink attached to the housing directly to reduce LED heats and add to life
- LED Driver: IP65/ Constant current
- External LED Driver (Junction Box Equiped , 3/4" NPT)
- Finish: White finish. Environmentally friendly polyester powder coatings.